



- ① 2"x2" TRIM
- ② 2"x8" CAP (TOP OF FENCE TO BE LEVEL)
- ③ 2" DIA. ~ S.S. 20 GALV. POST WITH CAP. POST SHALL BE FLUSH WITH BOTTOM OF 2"x6" CAP.
- ④ 1"x6" PICKET
NOTE: TO BE 3" ABOVE FINISH GRADE TYP.
- ⑤ (3) 2"x4" RAILS.
- ⑥ WACKER CLAMPS WITH COUNTER-SINK NUTS.
- ⑦ COMPACTED SOIL.
- ⑧ 12" DIA. CONCRETE FOOTING.
- ⑨ "U" BOLTS

NOTES:

- 1. FENCE TO BE REDWOOD OR CEDAR
- 2. HARDWARE TO BE HOT DIPPED GALV.
- 3. FENCE STAIN TO BE DETERMINED.

COLUMN DESIGN:

- 1. BRICK COLUMNS SHALL BE SPACED @ 32' ON CENTER MAX.
- 2. BRICK COLUMNS SHALL BE PLACED ON 18" DIA. DRILLED PIERS REINFORCED WITH 4-#4 BARS (BARS ARE TO BE CONTINUOUS THROUGH BRICK COLUMN) #2 SPIRAL REINFORCING WITH 12" PITCH (PIERS ONLY).
- 3. COLUMN CAP SHALL BE PERMANENTLY ATTACHED TO THE BRICK COLUMN BY THE USE OF STANDARD MASONRY ANCHORS.



**CITY OF
DECATUR**

PAVING CONSTRUCTION DETAILS
STANDARD WOODEN FENCE

REVISED MAR 2000

SCALE: N.T.S.

SHEET: **P-19**